

WHEEL LOCK RELEASE TOOL BMW

91372250

For loosening the wheel lock locking bolt.

- 3-claw puller
- 315 mm sliding rod with 1,35 kg hammer
- Operating key with special external profile
- 100% process-safe operation

Suitable for all BMW and MINI wheel lock locking screws with rotating outer ring.













AXLE EASY BOOTS 79 - 110 MM

90446080 / 90446090

Universal set for time-saving replacement of defective axle boots without removing the drive shafts and other attachments.

The special & patented grooving system guarantees an absolutely firm hold of the bonding area.

The axle boots are available in 2 sizes:

90446080 for drive shaft joints from Ø 79 - 89 mm

90446090 for drive shaft joints from Ø 90 - 110 mm

RUBBER PLATE

90025601

Rubber plate Ø 125 mm enables precise support of all car parts under the vehicle.





PICHLER

PICHLER

JULY / AUGUST

XS-MULTI IMPACT WRENCH INCL. 5 PLUG IN ADAPTERS

80303000

Multifunctional mini air impact wrench with plug in adapters.

The 14 mm inner hex drive allows the following insert adapters to be used:

8 mm Bit drive x 14 mm 10 mm Bit drive x 14 mm 34" drive x 14 mm

3/8" drive x 14 mm

½" drive x 14 mm Extension 14 mm

The plug-in adapters can be adapted into the extension if required.

One-hand operation!

The 3-step speed control as well as the right-left change-over switch can be operated with only one hand.











Related products:

XS- IMPACT SOCKET SET 15 PCS. 8 - 22 MM

80303005

Impact Socket:

8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22 mm x 14 mm drive Box with foam

€ 79,90 ext



UNIVERSAL INJECTOR REMOVAL TOOL E.G. BMW

60383005

Injector removal tool for safe removal of Bosch injectors with piezo control, installed e.g. in BMW engines.

The double fixing grip reduces the risk of shearing off the injector above the cylinder head.









OPEN SOCKET SET
FOR HIGH-PRESSURE CONNECTIONS,
17 / 18 / 19 MM

60561725

Universal socket spanner set for loosening and tightening high-pressure line screw connections.

The extra-flat design of the socket spanners makes it possible to loosen the coupling nut even with a very narrow pipe radius. The nut is loosened via the 27 mm external hexagon. The cap nut is gripped on all 6 surfaces with a positive fit, which prevents consequential damage and reduces the risk of injury to the user.







UNIVERSAL INJECTOR SHAFT & SEAT BRUSHES SET

90391465

Universal Set for the professional cleaning of the Injector Shaft and the upper Seat of the Injector in the Cylinder head. Includes:

- > 4 sealing plugs with setting tool
- > Holder for tube brushes with flexible bit holder 1/4" (custom made)
- > 12 brass tube brushes (3 of each; Ø18, 19, 12 and 24 mm)
- > 2 long brass tube brushes
- > 2 brass wire end brushes ø17 mm
- > Guide for brass wire end brush





PICHLER











20 TON HYDRAULIC INJECTOR REMOVAL SET M9R / M9T / R9M

60382095

Pulling force 20 tons

Application:For removing frozen common rail injectors from the cylinder head using 20 tons hollow piston cylinder. In case the injector breaks off during pulling on the lower screw connection can the additional pull spindles be used to pull out the rest of the injector. It is recommended that after successful removing the injector to recondition the injector shaft with our Cleaning Set 9038100.

M9R (2.0):Nissan: Primastar, Qashqai , X-TrailOpel: VivaroRenault: Espace IV, Grand Scenic II, Grand Scenic III, Koleos, Laguna II, Laguna III, Latitude, Megane CC, Megane II, Megane III, Scenic III, Trafic II, Vel Satis

M9T (2.3):Nissan: NV400, Opel: Movano, Renault: Master III

R9M (1.6):Mercedes C-class: C 180d / C 200dNissan: Qashqai, X-TrailOpel: VivaroRenault: Espace V, Fluence, Grand Scenic III, Kadjar, Megane CC, Megane III, Mégane IV, Scénic III, Talisman II, Trafic, TraficIII

Related products:



COMPLEMENT TO INJECTOR REMOVAL KIT M9R, WITH OP-TIONAL CLEANING KIT 60385190



SOFIM ENGINE BRIDGE FOR IVECO DAILY, PEUGEOT BOXER, CITROEN RELAY, MITSUBISHI FUSO CANTER FOR INJECTOR REMOVAL

60385350



HYDRAULIC HAND OPERATED PUMP SET 3 PCS.

80255500

MONTH DEAL OF THE MONTH



RIM ERASER DISCS SET 6 PCS. INCL. DRILL CHUCK ADAPTER

82051010

Conical eraser disc for easy and quick removal of adhesive residues from wheel weights on aluminium rims.

rpm: 500 -max. 4000 Discs Ø: 60 mm

Scope of delivery: 6 pcs. eraser discs 1 pc. Drill Chuck Adapter




INNER RIM CLEANER

61495200

Inner Rim Cleaner is meant for the optimal cleaning of the inner wheel contact surface. It prevent corrosion related distortion of wheel bolt tightening torque.

€ **59**,90 ex ta





BRAKE LINE STRAIGHTENING TOOL UNI

61339050

- > Alignment tool for brake lines Ø 4.75 mm
- > 16 ball bearing mounted rollers
- > Damage-free alignment of the brake line
- > 2 long brass tube brushes
- > Very time saving application
- > New design: The rollers can be readjusted manually if necessary





MINI RATCHET PIPE CUTTER 31210300

Handy pipe cutter for all brake pipes 4.75 mm. Ratchet mechanism facilitates the cutting process. Particularly suitable for:

- Application directly on the vehicle
- > Application at working positions which are difficult to access
- > Cutting roll goods brake lines to length

PICHLER

HEX KEY 110°

52528100

- 110° angle adjustment
- XL-extra long blade design
- Ball head
- Extra short key head
- Allen key: 1.5, 2, 2.5, 3, 4, 5, 6, 8, 10 mm

Related products:

52528007 Hex Key 7 mm 110° (e.g. VW brake caliper)




MAGNETIC KEY SET EXTRA LONG



EXTERNEL THREAD DEBURRER TOOL

30640005 / 30640010



Also suitable for 12.9 screws. Works ideally up to max. 400 rpm

30640005 Deburrer from Ø 3 mm to 19 mm **30640010** Deburrer from Ø 15.0 mm to 36 mm







UNIVERSAL SLIDE HAMMER MOD. MASTER

61488005

The impact hammer is used, for example, for dismantling stuck fuel injectors, removing wheel hubs and bearings and rough dent removal in the bodywork area.

Very universal application by screwing on different thread adapters.





Slide hammer 8.5 kg with handle Weight: 8.5 kg Connecting-outside thread: M18x1.5

Rod length: 430 / 650 / 860 mm

INJECTOR ADAPTER SET

60384660

Adapter set for removing Bosch, Denso, Siemens / Continental and Delphi injectors.

Suitable to our Universal Hydraulic Injector Puller 61488005.





BALL JOINT ADAPTER

6038424

Using this ball joint adapter allows for greater control of the slide hammer and prevents thread damage if swung slightly off vertical and can allow easier access in tight situations.

Thread size IT M18x1.5 & OT M18x1.5





AdBlue® PRESSURE TESTING KIT

61915430



Urea pressure gauge and refractometer for quick and easy diagnosis in case of error messages of the exhaust aftertreatment system. SCR system.

The refractometer gives a quick analysis of the quality of the urea and its composition (urea to water).



Your PICHLER Partner:

PICHLER Werkzeug GmbH

Pacherstraße 20, 6020 Innsbruck, Austria +43 512 344 552

at@pichler.tools



